



# GlassMaster and Scarab Electrical Specifications

Model	Phase	Volts	Amps	Watts	Max Temp °F	Wire Size	Receptacle
GP706	1 PH	115	15	1725	1650	12	5-15*
HOTSTART PRO	1 PH	115	15	1725	1700	12	5-15*
FIREBOX 14	1 PH	115	15	1725	1700	12	5-15*
FIREBOX 8	1 PH	115	15	1725	1725	12	5-15*
GMT/GM10F	1 PH	115	15	1725	1725	12	5-15*
GMT/GM814	1 PH	240	27.8	6660	1800	8	6-50
GMT/GM814	1 PH	208	32	6656	1800	8	6-50
GMT/GM1014	1 PH	240	34	8140	1800	8	6-50
GMT/GM1014	1 PH	208	39.1	8140	1800	8	6-50
GMT/GM1214-3	1 PH	240	42	10000	1800	6	6-50**
GMT/GM1214-3	1 PH	208	48	10000	1800	6	6-50**
GMT/GM1214-3	3 PH	240	29	10000	1800	8	15-50
GMT/GM1214-3	3 PH	208	29.4	10000	1800	8	15-50
GMT/GM1414	1 PH	240	34.7	8320	1800	8	6-50
GMT/GM1414	1 PH	208	40	8320	1800	8	6-50
GMT/GM1414	3 PH	240	20	8320	1800	10	15-50
GMT/GM1414	3 PH	208	23.1	8320	1800	10	15-50
GMT/GM818	1 PH	240	26.7	6400	1800	8	6-50
GMT/GM818	1 PH	208	26.7	5500	1800	8	6-50
GMT/GM1018	1 PH	240	39.4	9460	1800	8	6-50
GMT/GM1018	1 PH	208	40	8320	1800	8	6-50
GMT/GM1227-3	1 PH	240	48	11520	1800	6	6-50**
GMT/GM1227-3	1 PH	208	48	9984	1800	6	6-50**
GMT/GM1227-3	3 PH	240	29.3	11520	1800	8	15-50
GMT/GM1227-3	3 PH	208	31.7	11000	1800	8	15-50
GMT/GM22CS	1 PH	240	31	7450	1800	8	6-50
GMT/GM22CS	1 PH	208	35.8	7450	1800	8	6-50
GMT/GM22CS	3 PH	240	17.9	7450	1800	10	15-50
GMT/GM22CS	3 PH	208	20.7	7450	1800	10	15-50
GMT/GM818-3CR	1 PH	240	30	7200	2350	8	6-50
MICRO SCARAB	1 PH	115	14.3	1650	1700	12	5-15
MINI SCARAB	1 PH	240	16	3840	1700	12	6-20
SCARAB	1 PH	240	27	6480	1700	8	6-50
SCARAB XL	1 PH	240	48	11500	1700	6	6-50**

SPECIFICATIONS